

RAMROD

COMPACT MINI SKID LOADER SOLUTIONS



RAMROD MODEL 1350



MODEL 1330



MODEL 930



MODEL 575

For over 30 years, RAMROD has engineered and manufactured material handling solutions for construction, demolition, underground mining, fencing, agriculture, irrigation, and hundreds of other applications. With over 70 attachments the RAMROD product line can help benefit your business with compact, labour saving solutions. Call today or visit us online to discuss your needs!

1-800-667-1581

(306) 786-2600

sales@ramrodequip.com

www.RAMRODEQUIP.com

RAMROD FEATURES

- 3 year warranty
- 30 degree bucket rollback angle
- Full 85 degree dump angle
- Greaseable pivot points
- Easy single hand palm steering
- Easy serviceability
- High machine under clearance
- SAFER, self-levelling loader arms
- Powder paint finish
- All day fuel tanks
- Full 360 degree operator visibility
- Choice of gasoline or diesel engines
- Exclusive RAMROD rigid track system
- Narrow width
- Choice of tracks or wheels
- Over 70 attachments available
- Competitive financing/leasing options

CALL US TODAY!

SPECIFICATIONS:

Tractive (push-pull) capacity 1700 lbs (771 kg)
 Tipping capacity 1350 lbs (614 kg)
 Carrying capacity 2700 lbs (1227 kg)
 Lift height (to hinge pin) 72" (183 cm)
 Auxiliary hydraulic flow 12 GPM Gas
 14 GPM Diesel
 Hydraulic pumps 1
 Track size9" (23 cm)
 Self-levelling loader arms Standard
 Body height51.5" (130.8 cm)
 Length with bucket86.4" (219 cm)
 Ground clearance6.5" (17 cm)



**RAMROD PRO
SERIES 1350**

SPECIFICATIONS:

Tractive (push-pull) capacity 1450 lbs (658 kg)
 Tipping capacity 1330 lbs (604 kg)
 Carrying capacity 2660 lbs (1209 kg)
 Lift height (to hinge pin) 72" (183 cm)
 Auxiliary hydraulic flow 12 GPM Gas
 14 GPM Diesel
 Hydraulic pumps 1
 Track size6" (15 cm) or 9" (23 cm)
 Self-levelling loader arms Standard
 Body height50.5" (128.3 cm)
 Length with bucket81.5" (207 cm)
 Ground clearance6.5" (17 cm)



**RAMROD PRO
SERIES 1330**

SPECIFICATIONS:

Tractive (push-pull) capacity 1100 lbs (499 kg)
 Tipping capacity 930 lbs (422 kg)
 Carrying capacity 2000 lbs (907 kg)
 Lift height (to hinge pin) 72" (183 cm)
 Auxiliary hydraulic flow 12 GPM
 Hydraulic pumps 1
 Self-levelling loader arms Standard
 Body height 50.5" (128.3 cm)
 Length with bucket 81.5" (207 cm)
 Ground clearance 6.5" (17 cm)

**RAMROD PRO
SERIES 930**



OVER 70 ATTACHMENTS TO CHOOSE FROM!

RAMROD ESTATE SERIES 575T & 500

SPECIFICATIONS:

	575T	500
Tractive (push-pull) capacity	.995 lbs (452 kg)	995 lbs (452 kg)
Tipping capacity	.575 lbs (262 kg)	500 lbs (227 kg)
Carrying capacity	.975 lbs (443 kg)	825 lbs (375 kg)
Lift height (to hinge pin)	.66" (168 cm)	66" (168 cm)
Auxiliary hydraulic flow	.6.3 GPM	6.3 GPM
Self-levelling loader arms	.Standard	Standard
Body height	.48.5" (123.2 cm)	48.5" (123.2 cm)
Length with bucket	.77.5" (149.9 cm)	77.5" (149.9 cm)
Weight	.1380 lbs (627 kg)	1150 lbs (500 kg)
Ground clearance	.4.75" (12.07 cm)	4.75" (12.07 cm)



**RAMROD
WB1630TX**

SPECIFICATIONS:

Tractive (push-pull) capacity 1200 lbs (545 kg)
 Tipping capacity 1250 lbs (567 kg)
 Carrying capacity 2000+ lbs (1000+ kg)
 Lift height (to hinge pin)66" (167.6 cm)
 Auxiliary hydraulic flow 12 GPM
 Hydraulic pumps 1
 Self-levelling loader arms Standard
 Body height45.5" (115.6 cm)
 Length with bucket83.5" (212.1 cm)
 Ground clearance5" (12.7 cm)

ASK ABOUT CUSTOM UNITS!

**ROOFER UNIT
DEMOLITION UNIT
REMOTE CONTROL UNIT
PROPANE OPTION**

HEAVY DUTY